Acoustic Panels



Brand: Zintra



Acoustic Panels







3D Panel Batten 6 Detail

Acoustic Panels

Zintra 3D Panels Batten 6 offer both an intriguing design element and functional acoustic enhancement. Add depth and design to flat surfaces which absorb sound and cancel out soundwaves.

✓ Acoustic	Bleach Cleanable	✓ Easy Clean
✓ Easy Install		
Description	Seamlessly joined, our 3D Wall Panels offer both an intriguing design element and functional acoustic enhancement for straight or curved walls. These narrow panels boast a small pattern repeat, facilitating easy adjustment for wall-to-wall fitting without the need for custom drawings.	
	pattern. Designed to bring a touch of your space. Featuring alternating wid	timeless appeal of the board and batten f architectural elegance and visual interest to de boards and vertical battens, this captivating red surface. Its classic yet versatile design

Also Available in Batten 2, Batten 4 and Peaks design

effortlessly adds a sense of depth and character to any project.

Our **Peaks** design resembles the peaks of mountains. This panel features a series of angular protrusions arranged in a symmetrical pattern, creating a dynamic and textured surface. Its narrow profile and intricate design make it suitable for a variety of applications, from modern offices and conference rooms to contemporary residential settings.

Not only does the Peaks Panel contribute to the aesthetics of a space, but it also serves a functional purpose by enhancing sound absorption and cancelling out soundwaves. Its sculptural form adds depth and dimension to flat surfaces, transforming them into visually captivating focal points.

Not suitable as a free standing product.

Dimensions	Batten 6:	
	• 3 strips / set, 2.5m² (27SF)	
	• 305mm (12") w x 2745mm (108.1") h x 37mm (1.5") d / strip	
Composition	Zintra Acoustic Panel - 100% Solution Dyed (Colour Through) Polyester	
	12mm (1/2") -Density 2.4 kg /m² 0.5 lb/ft²	
Sustainability	Zintra is made from 100% recyclable materials.	
	 60% post-consumer recycled content from PET bottles. 	
	• 35% pre-consumer recycled content from PET chips	
	5% polylactic acid (PLA)	



Acoustic Panels

Fire Rating	ASTM-E84 – Class A classification AS ISO 9705 – 2003 – Group 1 classification EN-13501 – B-s2-d0 classification
Warranty	Visit FAQ for more details.
Assembly & Delivery	Refer Installation instructions for screw locations and spacing (screws not included).
	Recommended 2 People assembly
	Go to the Technical Documents and download the Installation Guide for more details.
Supplied As	Batten 6 3 Strips (Set) 2.5m² (27SF)
Suggested Installation	Go to Technical Documents and download the Installation Guide for more details.
How to Specify	1. Select Design
	2. Select Zintra Colour
Care Instructions	Vacuum to remove dust.
	Dab Zintra with a damp clean cloth and mild solution of liquid detergent and warm water. Repeat using only clean water, then pat dry with a lint free cloth.
	For difficult stains, use a solution of household bleach (10% bleach / 90% water). To remove the bleach, repeat using a clean, water dampened cloth, then pat dry.
	Always test in an inconspicuous area first and if you don't see the expected results, contact us.
Customisable	Zintra Acoustic Panel - 100% Solution Dyed (Colour Through) Polyester
	12mm (1/2") - Density 2.4 kg /m² 0.5 lb/ft²
Additional Comments	NRC 0.45



Color & Finish Options

Zintra 12mm Solid PET





zintraacoustic.com



Acoustic Panels





Storm







Zintra Timber Print









Eucalyptus

Ironbark

Spotted Gum