Acoustic Panels



Brand: **Zintra**

Collections: Pattern Panel

Applications: Ceilings, Walls



Acoustic Panels



Pattern Panel Links

2 of 7

Acoustic Panels

Discover the 51 classic and contemporary designs available in Zintra Pattern Panels. Effortlessly elevate your space with style, texture, and superior sound absorption with Pattern Panel Links.

✓ Acoustic✓ Easy Install	✓ Bleach Cleanable	✓ Easy Clean
Description	Zintra Patterns offers a broad range of classic or contemporary panel designs that can be used on their own, or in conjunction with Zintra backing, to create beautiful, acoustic screens and wall coverings.	
	Zintra and paired with a matching o achieve a unique aesthetic for walls	ons, each pattern can be intricately cut of out r contrasting solid Zintra backing panel to or ceilings. Experience enhanced noise ile enjoying a broad range of neutral and
	Links, is inspired by art deco	
	Choose from 51 designs.	
	Devraj Elephanta Fishbone Folia Hex Indus Jacks Kali Kerala K Marquise Monsoon Nadu Noktal	narata Bhushan Circuit Cirque Deepak ge Gadiva Garden Art Ginkgo Haimati rishnan Links Lost Malini Mandava ar Origami Padmesh Perdita Pivot Pixel an Sanskrit Setro Shard Siptical Stone dic Wamika
	Not suitable as a freestanding produ	uct.
	Elevate your environment with style a harmonious ambiance with superi	e, texture, contrast, and depth, all while creating or sound absorption.
Composition	Zintra Acoustic Panel - 100% Solutio	on Dyed (Colour Through) Polyester
	12mm (1/2") - Density 2.4 kg /m² 0.5	5 lb/ft²
	24mm (1") - Density 3.6 kg/m ² 0.75	5 lb/ft²
Sustainability	Zintra is made from 100% recyclable	e materials.
	• 60% post-consumer recycled content from PET bottles.	
	• 35% pre-consumer recycled content from PET chips	
	• 5% polylactic acid (PLA)	



Acoustic Panels

Dimensions	Pattern Only		
	1220mm (48") x 2745mm (108') x 12mm (1/2")		
	Pattern on Backer		
	1220mm (48") x 2745mm (108') x 24mm (1")		
Fire Rating	ASTM-E84 – Class A classification AS ISO 9705 – 2003 – Group 1 classification EN-13501 – B-s2-d0 classification		
Supplied As	Ships Flat Pack		
	Go to the Technical Documents and download the Installation Guide for more details.		
Suggested Installation	Go to Technical Documents and download the Installation Guide for more details.		
Care Instructions	Vacuum to remove dust.		
	Dab Zintra with a damp clean cloth and mild solution of liquid detergent and warm water. Repeat using only clean water, then pat dry with a lint free cloth.		
	For difficult stains, use a solution of household bleach (10% bleach / 90% water). To remove the bleach, repeat using a clean, water dampened cloth, then pat dry.		
	Always test in an inconspicuous area first and if you don't see the expected results, contact us.		
Warranty	Visit FAQ for more details.		
Customisable	The Zintra Acoustic Solutions range is customisable to your project. Please get in touch with your local contact for details.		



Acoustic Panels

Additional Comments Patterns Only NRC Rating

- Directly Mounted: 0.45
- With 2" (50mm) Air Gap: 0.85
- With 6" (152mm) Air Gap: 0.90
- With 12" (305mm) Air Gap: 0.95

Patterns on Backer NRC Rating

- Directly Mounted: 0.75
- With 2" (50mm) Air Gap: 0.95
- With 6" (152mm) Air Gap: 1.0
- With 12" (305mm) Air Gap: 1.0

How to Specify

- 1. Select Pattern design
- 2. Select Pattern only or Pattern on Backer.
- 3. Select Zintra Colour.

If selecting backer please state which colour is the pattern layer and which is the backer.



Color & Finish Options

Zintra 12mm Solid PET

zintraacoustic.com





6 of 7

Acoustic Panels

