

CONNECT PRISMATIC

Ceilings - Zintra Baffles



Texture: 3

Lustre: 1

Transparency: 2

DESCRIPTION / FEATURES	Add sculptural on-trend geo-accents to your ceiling space with Baffles Connect. An innovative solution to large areas requiring improved acoustics, Connect Baffle options are designed with full ceiling coverage in mind and will create a ceiling space with architectural shape, form and definitive character. Check out the Zintra 12mm color range here or the DOWNLOAD tab below for a pdf.
HOW TO SPECIFY	1. Zintra color 2. Design
COMPOSITION	Zintra Acoustic Panel - 100% Solution Dyed (color through) Polyester
FINISHES AVAILABLE	Zintra Plain 1/2" (12mm) Color Range Zintra Timber 1/2" (12mm) Color Range
STANDARD SIZE	18 triangles / set, 16.9 SF (1.7m²) 30.2" (768mm) w x 88.2" (2241mm) d x 4.7" (120mm) h
INDOOR/OUTDOOR	Indoor only
WET AREAS	No
SUGGESTED INSTALLATION	Check out the DOWNLOAD tab for a complete Handling and Installation guide.

	Baffle Connect components are supplied flat pack. Fix Adjustable Cable Kit to Ceiling. Assemble Connect on floor and hang by S-hooks. Adjust Cable Kit to complete Connect system.
CUSTOMISABLE	No. Designed for easy on site customisation.
THERMOFORMABLE	No
BRAND SPEC	ZINTRA
FIRE RATING	ASTM E-84 - Class A E-13501 - B-s2-d0 AS 5637.1:2015 - Group 1
ADDITIONAL COMMENTS	NRC - 0.90 Only available from Zindra Acoustic Panel 1/2" (12mm). Cloud systems include Adjustable Cable Kit. See images on website for hardware detail. Longer Cables, multi-color and Digital Print available for an additional fee.
FABRICATION	Stanley knife if required
REFINISHABLE	No
CARE INSTRUCTIONS	Remove spills immediately using damp, clean cloth. Dab Zindra with a clean, soft white cloth dampened with a mild solution of liquid detergent and warm water. Repeat using only clean water, then pat dry with a lint free cloth. Avoid using wax polishes, solvents or concentrated abrasives. For more difficult stains, dampen a soft white cloth with a solution of household bleach (10% bleach / 90% water). Dab gently. Repeat using only a clean, water dampened cloth to remove bleach

	concentration then pat dry with a lint free cloth. Always test in an inconspicuous area first. If care instructions don't deliver the expected results, cease cleaning method immediately and contact Baresque for assistance.
ENVIRONMENTAL INFORMATION	We believe in the sustainability of both our planet and our people. We do everything we can to minimise our environmental impact and create spaces that contribute to the wellness of the people that use them. Certified by Declare and HPD, Zintrac is made from 100% recyclable materials. It has low levels of volatile organic compounds and contains no formaldehyde. It's Red List Free and meets the Global Recycling Standard. Reducing noise levels, minimizing indoor air pollutants, easy cleaning and a Class A fire rating are just a few of the reasons that Zintrac is the perfect material for the green buildings of today and tomorrow.