



e hello@zintraacoustic.com

p +1 855 922 7377

Closed Rafter

New Releases - Ceilings - Zintra Baffles



Texture:

Lustre:

Transparency:

DESCRIPTION / FEATURES	The modular design is available in a range of configurations and come
	with connectors that let you tailor them to individual spaces.
	They're lightweight and come in a range of 24-colors, and realistic
	wood prints that give you the choice of creating anything from
	progressive ceiling features to exposed architectural beams.
	Available in 5 standard formats and designed with customisation in
	mind beams are easily configured for larger spaces.
	Beams have been specifically designed to offer superior acoustics by
	acting as a porous sound absorber across the full frequency range. If
	you are looking for added acoustic value, co-ordinated Coffer panels
	are available as an accessory to increase NRC rating up to 1.5
HOW TO SPECIFY	1. Select PET Color
	2. Select Size
FINISHES AVAILABLE	24 Colors – Ash, Bark, Brick, Cadet, Chambray, Cobalt, Ecru, Fossil,
	Frost, Grass, Greige, Ivory, Linen, Malachite, Mandarin, Midnight,
	Ochre, Olive, Pebble, Sky, Smoke, Sunshine, Tar.



	Zintra Plain 1/2" (12mm) Color Range
	4 Timber Prints - Eucalyptus, Iron bark, Merbau, Spotted Gum.
	Zintra Timber 1/2" (12mm) Color Range
	12 Premium Wood Prints - Australian Walnut, Cherry, Claro Walnut,
	Euro Beech, Knotty Pine, Lace Wood, Maple, Palm Wood, Poplar,
	Redwood, Rustic Walnut, White Oak.
	Zintra Premium Wood Prints
STANDARD SIZE	5 x 5 123" (3124mm) w x 8" (203mm) h x 123" (3124mm) d
	4 x 5 99" (2515mm) w x 8" (203mm) h x 123" (3124mm) d
	3 x 5 75" (1905mm) w x 8" (203mm) h x 123" (3124mm) d
	2 x 5 51" (1295mm) w x 8" (203mm) h x 123" (3124mm) d
	1 x 5 27" (686mm) w x 8" (203mm) h x 123" (3124mm) d
SUGGESTED INSTALLATION	Cable System
	Uni Strut Hanging System
	Screw into celing
FIRE RATING	ASTM-E84 - Class A classification
	AS ISO 9705 – 2003 - Group 1 classification
	EN-13501 - B-s2-d0 classification
ADDITIONAL COMMENTS	NRC 1.0
	NRC 1.5 With Coffers
CARE INSTRUCTIONS	Dab Zintra with a damp clean cloth and mild solution of liquid detergent
	and warm water. Repeat using only clean water, then pat dry with a lint
	free cloth.
	For difficult stains, use a solution of household bleach (10% bleach /
	90% water). To remove the bleach, repeat using a clean, water
	dampened cloth, then pat dry.
	Always test in an inconspicuous area first and if you don't see the



	expected results, contact us.
MATERIAL	Zintra Acoustic Panel - 100% Solution Dyed (Color Through) Polyester
WARRANTY	5 Years
MADE IN	USA
ASSEMBLY & DELIVERY	Ships Flat Pack
	Assembly Required
	Refer Installation Instructions
CUSTOMIZABLE	The Zintra Acoustic Solutions range is customisable to your project.
	Please get in touch with your local contact for details.