

CRAZE

Walls - Zintra Etch



Texture:

Lustre:

Transparency:

DESCRIPTION / FEATURES	<p>Acoustic absorption meets dynamic 3D design with Baresque's new Zintra Etch. Featuring a range of subtle textures, Zintra Etch will help deliver a cutting-edge but welcoming atmosphere to your next commercial, hospitality or institutional interior.</p> <p>Zintra Etch is available in an extensive range of understated to statement colours and will cultivate calming environs with this cost-effective sound and design solution. Zintra Etch is also easily able to tied back to plain Zintra sheets or talk to us about replicating your Etch pattern in Zintra on Zintra.</p> <p>Zintra Etch Features:</p> <ul style="list-style-type: none"> * Suitable for wall cladding or ceilings * NRC equals at least 0.45 * pattern matching with seamless hidden joins (excl VJ Angle and Kaleido) * 2795mm sheet size allows join-free floor-to-ceiling and easy fitout * Designs easily customised to suit your needs
HOW TO SPECIFY	<ol style="list-style-type: none"> 1. Design 2. Colour

COMPOSITION	Zintra Acoustic Panel - 100% Solution Dyed (Colour Through) Polyester
FINISHES AVAILABLE	Zintra Plain 1/2" (12mm) Color Range Zintra Timber 1/2" (12mm) Color Range
STANDARD SIZE	48" x 108" x 0.5" (1219mm x 2743mm x 12mm)
INDOOR/OUTDOOR	Indoor only
WET AREAS	No
SUGGESTED INSTALLATION	Adhere to substrate using contact adhesive or Liquid Nails. Panel can be mechanically fixed using details similar to glass fittings.
CUSTOMISABLE	The Zintra Acoustic Solutions range is customisable to your project. Please get in touch with your local contact for details.
THERMOFORMABLE	No
FIRE RATING	ASTM E-84 â€œ Class A E-13501 â€œ B-s2-d0 AS 5637.1:2015 - Group 1
ADDITIONAL COMMENTS	Etch is a 3mm deep V groove. Not suitable as a free standing product.
SUPPLIED AS	Full sheets for cutting to size on site as required
FABRICATION	Utility knife or CNC with an oscillating knife
REFINISHABLE	No
CARE INSTRUCTIONS	Remove spills immediately using damp, clean cloth. Dab Zintra with a clean, soft white cloth dampened with a mild solution of liquid detergent and warm water. Repeat using only clean water, then pat dry with a lint free cloth. Avoid using wax polishes, solvents or concentrated abrasives. For more difficult stains, dampen a soft white cloth with a solution of

	<p>household bleach (10% bleach / 90% water). Dab gently. Repeat using only a clean, water dampened cloth to remove bleach concentration then pat dry with a lint free cloth.</p> <p>Always test in an inconspicuous area first. If care instructions don't deliver the expected results, cease cleaning method immediately and contact Baresque for assistance.</p>
ENVIRONMENTAL INFORMATION	<p>We believe in the sustainability of both our planet and our people. We do everything we can to minimise our environmental impact and create spaces that contribute to the wellness of the people that use them.</p> <p>Certified by Declare and HPD, Zintrac is made from 100% recyclable materials. It has low levels of volatile organic compounds and contains no formaldehyde. It's Red List Free and meets the Global Recycling Standard.</p> <p>Reducing noise levels, minimizing indoor air pollutants, easy cleaning and a Class A fire rating are just a few of the reasons that Zintrac is the perfect material for the green buildings of today and tomorrow.</p>