



e hello@zintraacoustic.com

p +1 855 922 7377

RIDGE

Walls - Zintra Blades



Texture:

Lustre:

Transparency:

DESCRIPTION / FEATURES	Zintra Blades are prefabricated, wall mounted systems that showcase
	Zintra's flexible characteristics.
	Combining a dynamic aesthetic appeal and acoustic performance these
	systems are supplied ready to install with minimum fuss. A great
	advantage of the vertical blades is the increased surface area that is
	presented to the room resulting in a greater absorption of sound
	compared to flat panels (NRC = 0.9).
HOW TO SPECIFY	1. Design2. Size3. Zintra Colour
COMPOSITION	100% Solution Dyed (Colour Through) Polyester blades with mild steel
	tube
FINISHES AVAILABLE	Zintra Plain 1/2" (12mm) Color RangeZintra Timber 1/2" (12mm) Color
	<u>Range</u>
STANDARD SIZE	48" x 54" (1220mm x 1370mm)48" x 108" (1220mm x 2745mm)
INDOOR/OUTDOOR	Indoor only
WET AREAS	No



zintraacoustic.com

e hello@zintraacoustic.com

p +1 855 922 7377

SUGGESTED INSTALLATION	Insert tube into pre-cut holes in the blades.
	Move blades into correct position.
	Fix tube off to the wall with screws (not supplied).
CUSTOMISABLE	The Zintra Acoustic Solutions range is customisable to your project.
ENVIRONMENTAL INFORMATION	PVeatsæligeveim tthæchustthinyaduilithy callboothta or fooladetæilsd our people. We
THERMOFORMABLE	No everything we can to minimise our environmental impact and
FIRE RATING	ASTIM EpadesChauschEhrlindinette Brezvelnesson 7hte 20eto lectinatupsle
	them.
SUPPLIED AS	Pærtfäleddæytelbeladæsa,notblidt Pied Zuintræa is made from 100% recyclable
FABRICATION	bhtälterilahsteltona SNowwitheas outsoollatilegok galeic compounds and contains
REFINISHABLE	No formaldehyde. It's Red List Free and meets the Global Recycling
CARE INSTRUCTIONS	Rtandaedspills immediately using damp, clean cloth.
	Reduzimtganwiste sevlelan insioftwizhite inlattrodam perheta wish easyl die ahithigh
	andicalical control of the control o
	theerfepatrolartyeniathfoar Ithefoereenlookuildings of today and tomorrow.
	Avoid using wax polishes, solvents or concentrated abrasives.
	For more difficult stains, dampen a soft white cloth with a solution of
	household bleach (10% bleach / 90% water). Dab gently. Repeat using
	only a clean, water dampened cloth to remove bleach
	concentration then pat dry with a lint free cloth.
	Always test in an inconspicuous area first. If care instructions don't
	deliver the expected results, cease cleaning method immediately and
	contact Baresque for assistance.