Zintrcl®

zintraacoustic.com e hello@zintraacoustic.com p +1 855 922 7377

ZINTRA ACOUSTIC IN 12MM

Walls - Zintra Acoustic Panel



Texture: Lustre: Transparency:

DESCRIPTION / FEATURES	Baresque's Zintra Acoustic Panel is the perfect solution for your
	application where acoustic performance as well as aesthetics are
	required. Zintra's wide range of colours and ease of use make it the
	ideal material for commercial, hospitality and institutional projects.
	Zintra Acoustic Panel features include:
	* Cost effective sound solution - NRC = 0.45 for 12mm (1/2"), 0.75 for
	24mm (1")
	* 2800mm (110") long sheets ideal for join-free floor to ceiling
	applications
	* Broad range of neutral and bright colours
	* Suitable for a multitude of applications - walls, ceilings, screens
	* Easily fabricated and installed
	* Pinnable
HOW TO SPECIFY	1. Colour
COMPOSITION	Zintra Acoustic Panel - 100% Solution Dyed (Colour Through)
	Polyester
STANDARD SIZE	48.2" x 110.3" x 0.5" (1225mm x 2800mm x 12mm)
WEIGHT	2.4kg/m² (0.5lbs / sq. ft)
INDOOR/OUTDOOR	Indoor only
<u></u>	•

Zintrcl®

[1
WET AREAS	No
SUGGESTED INSTALLATION	Adhere to substrate using contact adhesive or Liquid Nails. Panel can
	be mechanically fixed using details similar to glass fittings.
ENSIROMISLEDIEL INFORMATION	We Zeheve Andbetisu Stalutabilisty auf geoits curst plaiset been to over un quipplie.c.We
	Processergetting to recoravito proininio salo contact founderates impact and
THERMOFORMABLE	breate spaces that contribute to the wellness of the people that use
FIRE RATING	統会TFM E-84 - Class A
	E-13501 - B-s2-d0
	Ser56ea7.by2Det5laneranonopHPD, Zintra is made from 100% recyclable
FABRICATION	bhaite,rikahsidetchra SN 600 whethe as not socillatile gok gale ic compounds and contains
REFINISHABLE	Nopformaldehyde. It's Red List Free and meets the Global Recycling
CARE INSTRUCTIONS	Btandaedspills immediately using damp, clean cloth.
	Bebuziimtgenwiste zeoleksn, nsioft nizhitg in dtood zim peltetawisth eensyl die aluiting n
	an bioqui didese. Agterret aat on gvaren juustterfeRvep tetteuserags comsty to bet a Zinvurates, the
	prestep a manual for lithe for each down in the second down in the sec
	Avoid using wax polishes, solvents or concentrated abrasives.
	For more difficult stains, dampen a soft white cloth with a solution of
	household bleach (10% bleach / 90% water). Dab gently. Repeat using
	only a clean, water dampened cloth to remove bleach
	concentration then pat dry with a lint free cloth.
	Always test in an inconspicuous area first. If care instructions don't
	deliver the expected results, cease cleaning method immediately and
	contact Baresque for assistance.